

CEMIMAX A2000

Very high strength for resilient floor coverings

Description:

Dispersion adhesive for resilient synthetic floor and wall coverings in interior areas.

Especially suitable for:

Rubber flooring sheet, PVC sport flooring sheet, vinyl tile and cushioned vinyl coverings, including those with textile fleece backings.

Product Properties:

- Stable quality Bonding, layer has durable resilience.
- Good water resistance, excellent bonding strength.
- Very high initial tack and final bonding strength.
- Easy application, high coverage rate.
- Low VOC

Binders:

Modified polyacrylate-copolymers with bond strengthening resins.

Technical Data: (Under normal conditions at 20°C.)

Packaging: 5kg,25kg Plastic drum

Shelf-life: Min. 12 months

Colour: Cream-white

Working temperature: +5°C - 35°C

Consumption: 3.75m²/1 Litres

Open time: 5-30 minutes

Working time: 1-2 hours

Set to traffic: After 24-48 hours

Final strength: After 5-7 days

Application:

- Allow primers and smoothing compounds to dry thoroughly. Refer to the product Data Sheet for the products used.

- Stir thoroughly the product before use, Apply it evenly on the surface of substrate by using A2 or A3 toothed trowel. After short open time of 5-30 min. the substrate is ready to accept above flooring material.
- After the flooring material is applied on the substrate rub the surface by wood plate or roll by roller to remove entranced air under the flooring material. Make sure that the adhesive has transferred to the back of the flooring material.
- The adhesive will be dried after 24h, and set to foot traffic after 48h.

Notes:

The product should be protected against frost and direct light during transportation, storage and application. Application temperature should not be lower than 5°C.

