

CEMIMAX DP70

Cemimax DP70 is a Low emission, multi-purpose dispersion primer for exterior use.

Description:

Dispersion Primer with a wide range of applications, for interior and exterior use, providing overlayment compound DL10 or DL59 is applied within drying time of primer. Not to be left exposed to the elements for more than 2 hours.

Especially suitable for:

Use on surfaces with well-bonded, waterproof adhesive and smoothing compound residues.

Product Properties:

- Ready to use.
- Excellent bond
- Rapid drying
- High coverage
- Solvent-free.
- Suitable for exterior use

Binders:

Modified styrene-acrylate copolymers, wetting- and defoaming-agents, preservatives and water.

Technical Data: (Under normal conditions at 20°C .)

Packaging: Plastic bucket

Packsize: 20 kg, 5 kg

Shelf-life: 12 months

Working temperature: +5°C - 35°C

Consumption: Approx. 12m²/1 Litre

Drying time: 4-6 hours

Touch Dry: 15-20mins

Application:

- The surface should be clean, dry, and strong without loose layer should be completely removed by granulator, and the substrate should be cleaned thoroughly.
- The product can be diluted with water. The water proportion base on the substrate situation.(note: if the existing substrate is ceramic tile, it shall not be diluted.)
- Apply the primer evenly to fully cover the surface using a fine-pored foam roller.

- Drying times: allow to dry to a clear, transparent, almost tack-free film. Dependant upon floor temperature and humidity, In favourable climatic conditions and on absorbent surfaces, a drying time of 1-3 hours is normally adequate.

Notes:

The product should be protected against frost and direct light during transportation, storage and application. Application temperature should not be lower than 5°C.